



PULZAR HYPERMAX FULLY SYNTHETIC SAE 5W-30

Premium synthetic motor oil which designed specifically for FORD Diesel and Gasoline engines

Product Descriptions

PULZAR HYPERMAX FULLY SYNTHETIC SAE 5W-30 is premium synthetic motor oil which designed specifically for All Ford latest generation Diesel engines (Always refer to the Ford manual or handbook for correct specification).

PULZAR HYPERMAX FULLY SYNTHETIC SAE 5W-30 exceeds the European performance requirements of ACEA A5/B5-10 classifications and meeting Ford WSS M2C 913-D. It provides the outstanding protection against engine wear, oxidation and prevents the formation of deposits and sludge. It has the special additives that provide the engine cleanliness and reduce friction result in utmost fuel economy.

Application

PULZAR HYPERMAX FULLY SYNTHETIC SAE 5W-30 is recommended for the latest generation Ford diesel and gasoline engines which require Ford WSS M2C 913-D. It is also backwards compatible with all engines requiring Ford WSS M2C 912-A, 913-A/B and 913-C.

Features

- Specific design for All ford vehicle which recommend Ford WSS M2C 913-D
- Compatibility with a comprehensive range of engines
- Utmost Fuel economy
- Ultimate protection against engine wear
- Prevention against the formation of deposits and sludge
- Outstanding thermal stability and resistance to oxidation
- Meets performance requirements of ACEA A5/B5-10 and Ford WSS M2C 913-D

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES PULZAR HYPERMAX FULLY SYNTHETIC SAE 5W-30

Test	METHOD	TYPICAL RESULTS
SAE Viscosity Grade	SAE J300	5W-30
ACEA		A5/B5-10
Colour	ASTM D-6045	L3.5
Flash Point (COC) °C	ASTM D-92	228
Density @30 °C	ASTM D-1298	0.8444
Viscosity		
@ 40°C cSt	ASTM D-445	51.24
@ 100°C cSt	ASTM D-445	9.540
Viscosity Index	ASTM D-2270	172
CCS@-30 °C	ASTM D-5293	4572
Total Base Number, mg KOH/g	ASTM D-2896	11.4

